

## Steca RCC-02/03

### Remote control and display (incl. 2m cable), accessories for Steca Xtender XTS, XTM and XTH

Lots of information on the status of the system can be retrieved using the graphic display of the Steca RCC. Any incidents within the system are also saved and displayed. This means that any problems which might occur are identified early.

Many values of the Steca Xtender can be set using the Steca RCC, such as the charging process of the battery charger, the programming of the multifunctional contacts and the various operating modes.

An SD card slot can be used for saving parameters, for the data logger or for updating the software.



#### Displays

- Multifunction graphical LCD display with backlighting

#### Operation

- Programming by buttons

#### Certificates

- Compliant with European Standards (CE)
- RoHS compliant
- Made in Europe

	RCC-02	RCC-03
<b>Fitting and construction</b>		
Degree of protection	IP 20	
Mounting	Surface-mounted	Flush-mounted
Dimensions (X x Y x Z)	170 x 170 x 46 mm	120 x 130 x 43 mm
Weight	400 g	268 g

Technical data at 25 °C / 77 °F



## Steca PA RC100

### Programming unit

The programming unit Steca PA RC100 allows to program Steca solar charge controllers. The values can be adjusted with the help of switches. After a restart of the charge controller the new settings can be activated by pressing the program-button on the Steca PA RC100. An LED will transfer the values to the controller.



#### Product features

- Low weight
- Simple use
- Maintenance-free
- Low own consumption
- Best reliability

	PA RC100
<b>Characterisation of the operating performance</b>	
Supply voltage	3 V (2 x 1.5 V AAA / R03 batteries)
Adjustable parameters	<ul style="list-style-type: none"> <li>– Type of battery: gel / liquid</li> <li>– Night light function</li> <li>– End of charge voltages (float / boost / equal)</li> <li>– Deep discharge protection (LVD)</li> <li>– LVD factor</li> <li>– Switch-on threshold</li> </ul>
Suitable for the following Steca charge controllers	<ul style="list-style-type: none"> <li>– Steca Solsum F</li> <li>– Steca Solarix PRS</li> <li>– Steca Solarix MPPT 1010/2010</li> <li>– Steca Solsum 2525/4040</li> </ul>
<b>Fitting and construction</b>	
Dimensions (X x Y x Z)	115 x 57 x 20 mm
Weight	90 g

Technical data at 25 °C / 77 °F